



**SPECIFICATION FOR CRYSTAL FILTER**
MCF 21.4-15BNumber: 91 750
Drawing: 61 9574**1. Electric values**

- 1.0 Number of poles : 4
- 1.1 Nominal centre frequency f_{nom} : 21.4 MHz
- 1.2 Bandwidth between 3 dB frequencies : $\geq \pm 7.5$ kHz
- 1.3 Ripple at $f_{nom} \pm 6.0$ kHz : ≤ 1.0 dB
- 1.4 Insertion loss : ≤ 2.0 dB
- 1.5 Stop band: $f_{nom} \pm 25$ kHz : ≥ 40 dB
 $f_{nom} + 350 \dots + 1000$ kHz : ≥ 65 dB
 $f_{nom} - 200 \dots - 1000$ kHz : ≥ 80 dB
- 1.6 Terminating impedance (input and output) : 1500 Ohm // 2.0 pF
Coupling capacitance : 8.0 pF
- 1.7 Operating temperature range : -30°C až $+70^\circ\text{C}$
- 1.8 Case : 2 x UM-1
- 1.9 Marking on the case :

KRYSTALY
21.4-15B
YYWW

YY = year
WW = week

2. Characteristics MCF 21.4-15B**Dimensions [mm]**
Case UM-1**Measurement Circuit**

edited	23.02.2011	P. Seidl
--------	------------	----------